

55

310382



Superior Drum and Barrel

© 2013 Google

Go









610-09

ORGANIC PEROXIDE TYPE F LIQUID
(TERT-BUTYL HYDROPEROXIDE) < 72% WITH > = 28% WATER

USP-800

UN 3109

INDUSTRIAL USE ONLY MUST STORE BELOW 38 DEG C (100 DEG F)

OXIDIZING MATERIAL. KEEP AWAY FROM HEAT AND FIRE. DO NOT STORE WITH
HARMFUL OR FATAL IF SWALLOWED. EYE IRRITANT. AVOID BREATHING
HARMFUL. WEAR CHEMICAL SPLASH GOGGLES, PROTECTIVE CLOTHING AND
GLOVES WHEN HANDLING THIS MATERIAL.

Protect from light, heat, sparks, and flames. Do not mix with hot materials. Prevent
contamination with foreign materials, especially readily oxidizing materials and accelerators.
Improper storage conditions can cause violent decomposition, leading to fire or loss of activity.
When the container is opened, it must be destroyed by ventilation and must not be reused for
any purpose. Dispose of contents in accordance with local, State and Federal regulations. Read Material Safety Data Sheet prior to use. The manufacturer does not
make any warranty as to the finished product in which this material is used.

EYES: IMMEDIATELY FLUSH WITH LARGE QUANTITIES OF WATER FOR AT LEAST
15 MINUTES AND THEN CALL A PHYSICIAN. MAY CAUSE BLINDNESS.
SKIN: WASH WITH SOAP AND WATER. IF IRRITATION OCCURS, SEE A PHYSICIAN.

INHALATION: REMOVE TO FRESH AIR. CONSULT A PHYSICIAN IF DISCOMFORT PERSISTS.
SWALLOWED: ADMINISTER LARGE QUANTITIES OF WATER IF PERSON IS CONSCIOUS.
NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.
IMMEDIATELY CONTACT A PHYSICIAN.

KEEP OUT OF REACH OF CHILDREN

Witco, a subsidiary of CROMPTON
CORPORATION, New York and Bureau
Road Marshall, Texas (USA)

CHEMTREC
Day or Night
1-800-424-9300

or call
Witco, a subsidiary of
Crompton Corporation
(903)-938-5141

IMDG CODE PAGE: 5229
CAS NO. 75-91-2

RECOMMENDED STORAGE BELOW
20 DEG C (68 DEG F)

REV. 5/00

190 KGS
419 LBS

BATCH #203547
MATERIAL # 15953



FLAMMABLE LIQUID
NOS BLDG 401 TRD UN199
DRUM #44 DATE 7-05
CONTENTS FOR DELIVERY
Hazard







